



Scotch® General Purpose Masking Tape 3060

Product Data Sheet

Updated : June 2003
Supersedes : New

Product Description Scotch™ Tape 3060 is a chamois coloured creped paper masking tape designed for a wide variety of applications throughout the industrial market.

Physical Properties Not for specification purposes	Adhesive Type	Crosslinked rubber resin adhesive
	Backing	Latex saturated creped paper backing
	Thickness AFERA 4006	0.135 mm
	Tape Colour	Chamois
	Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity

Performance Characteristics Not for specification purposes	Adhesion to Stainless Steel AFERA 4001	6 N/25 mm
	Tensile Strength AFERA 4004	88 N/25 mm
	Elongation at Break AFERA 4005	10%
	Temperature Performance	60°C

Additional Product Information Satisfactory performance and clean removal of Scotch® Tape 3060 will be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch® Tape 3060 performance parameters in your process conditions. The optimum level for product performance and easy removal is at 60 °C for 60 min.

Updated : June 2003
Supersedes : New

Application

Scotch® Tape 3060 is a utility purpose paper tape for fixing-, bundling-, holding- and sealing applications as well as for short term paint masking and other uses up to a temperature of 100 °C for one hour.

Storage Conditions

Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.

FEATURES

Latex saturated creped paper backing

ADVANTAGES

Conformability
Thinness
Solvent resistance
Easy hand tear
Easy unwind
Good paint anchorage
Sliver resistance
Instant adhesion
Good holding power

BENEFITS

Good curve masking
Reduces paint build-up and provides good paint lines
Prevents paint bleed through
Good handling
Nice handling
Good paint flaking resistance
Easy removal
Sticks easily
Resists lifting

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

**Tapes & Adhesives**

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
3M House,
28 Great Jackson Street,
Manchester,
M15 4PA

Product Information :
Tel 0870 60 800 50
Fax 0870 60 700 99

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

Customer Service :
Tel (01) 280 3555
Fax (01) 280 3509