



The Glue People

Trade Grade Products Ltd
Unit 2, Thorne Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6FB

Tel 01202 820177
Fax 01202 814011

D154

Single sided PVC foam.

TYPICAL APPLICATIONS

Applications include the sealing of:

- Roofing and cladding seals
- Profiled sheeting
- All types of glazing systems
- Sealing partition walls
- Heating and ventilation seals
- Vehicle body work
- Cold bridging in roofing and cladding
- Access doors
- Gutter joints
- Coldroom panels
- Prefabricated tanks
- Building panels
- Rooflights
- Greenhouses

TECHNICAL INFORMATION

	20 Series	25 Series	50 Series
Adhesive	Acrylic	Acrylic	Acrylic
Colours	Black / White	Black / Grey	Black / Grey
Density (kg/m³)	100	150	200
Shore hardness (00 Scale)	20	35	50
Tensile strength (kPa)	240	240	640
Elongation	> 100%	> 100%	> 120%
Service temperature		-30°C to +70°C	
Application temperature		+10°C to +45°C	
UV resistance		Excellent	
Fungi resistance		Excellent	
Oxidation resistance		Excellent	
Weather resistance		Excellent	
Shelf life		1 Year	

This product meets the following 'Surface Spread Of Flame Requirements' ; FMVSS302, DIN4102 Class B2.

GENERAL INFORMATION

Data Ranges

The data contained herein may be reported as a typical value and/or range. Values are based on actual test data and are verified on a periodic basis.

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.