



The Glue People

Trade Grade Products Ltd
Unit 2, Thorne Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6FB

Tel 01202 820177
Fax 01202 814011

H964

Double coated UPVC tape.

GENERAL DESCRIPTION

A double coated UPVC adhesive tape, which has found a wide variety of uses in the following industries:

- Furniture manufacture / repair
- Splicing
- Plastic Film
- Paper, foil, etc
- Name plates
- Labels
- Emblems
- Metal and Plastic trim mounting
- Automotive repair
- Plus many more

TECHNICAL INFORMATION

Adhesive	Acrylic
Tack	J. Dow No. 22
Liner	60# 90gsm Honey Glassine
Carrier	Un-plasticised PVC
Peel Adhesion	PSTC-3 over 1.3 kg / 25mm
Sheer Strength	PSTC-7 over 72 hours with 1 kg loading on stainless steel plate of 25mm x 25mm
Thickness	0.22mm \pm 0.01mm
Heat Resistance	PSTC-9 60°C over 24 hours with 0.5 kg loading on stainless steel plate of 25mm x 25mm

GENERAL INFORMATION

Data Ranges

The data contained herein may be reported as a typical value and/or range. Values are based on actual test data and are verified on a periodic basis.

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.