



The Glue People

Trade Grade Products Ltd
Unit 2, Thorne Way
Woolsbridge Industrial Park
Three Legged Cross, Wimborne
Dorset, BH21 6FB

Tel 01202 820177
Fax 01202 814011

Tradebond H55

High quality tube winding adhesive.

GENERAL DESCRIPTION

Tradebond H55 is a high quality water based adhesive, formulated for use with paper, card and as a tube winding adhesive.

TECHNICAL INFORMATION

Colour	White
Density	1.1 (approx)
Physical state	Liquid
Solids content	25% – 28%
Viscosity	1800 mPa.s
pH	4.5
Chemical base	Synthetic polymer

PACKAGING

Tradebond H55 is available in

- 25Kg Drums
- 205Kg Tight-head Drum
- 1000Kg IBC

GENERAL INFORMATION

For safe handling information on this product, consult the material safety data sheets, (MSDS).

Storage

*****PROTECT FROM FROST***** Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 5°C and 30°C. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container. Use oldest stock first. For specific shelf-life information, contact Trade Grade Products at the above address.

Data Ranges

The data contained herein may be reported as a typical value and/or range. Values are based on actual test data and are verified on a periodic basis.

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, Tradebond H55.