



The Glue People

Trade Grade Products Ltd
Unit 2, Thorne Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6FB

Tel 01202 820177
Fax 01202 814011

Tradebond WA29359

Formulated synthetic emulsion adhesive.

Product Description

Tradebond WA29359 is a one part synthetic emulsion adhesive, formulated for applications where a rapid grab and fast bond development are beneficial; including paper and board laminating, case and carton manufacturing and sealing, cigarette tipping, bag and sack manufacturing and glass bottle labelling. Tradebond WA29359 exhibits high tack, fast setting speed and a short open time.

Characteristics

- High initial tack.
- Fast setting speed.
- Rapid grab assures securely held bonds on initial combination.
- Fast bond development ensures rapid bonds and enables quick further conversion.

Application

The adhesive, substrate and ambient temperature should ideally be a minimum of 20°C. WA29359 can be applied using roller, wheel and extrusion systems. It is also suitable for use in cigarette tipping machines (Molins, Hauni, etc).

Shelflife

For best results; use within 3 months from the date of delivery. Rotate stock using oldest first. Keep covered to prevent contamination and drying out. Do not mix with other adhesive. **PROTECT FROM FROST.**

Technical Data

Base:	Synthetic emulsion adhesive
Appearance:	White liquid
Consistency:	Medium viscosity
Viscosity @ 23°C:	2300 mPa.s (Spindle 3, Speed 20rpm).
Solids content:	51 ± 1% (30 minutes @ 130°C)
Specific gravity:	1.10
pH value:	5.1
Cleaning:	Equipment should be cleaned with warm or cold water while the adhesive is still wet.

Labelling

No danger labelling required.

Information

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, Tradebond WA29359.