



*The Glue People*

**Trade Grade Products Ltd**  
Unit 2, Thorne Way  
Woolsbridge Industrial Park  
Three Legged Cross  
Wimborne, Dorset, BH21 6FB

Tel 01202 820177  
Fax 01202 814011

# Tradebond WA889

**Quick setting, versatile rubber latex adhesive**

## General Description

Tradebond WA889 is a formulated rubber latex adhesive (ammonia stabilised) designed for application by roller applicator or multi-stencil gummer. Not suitable for use with brass equipment.

## Application

Suitable application areas include:

- Envelope self sealing.

## Physical Data

Base	Rubber latex
Total Solids	59%
pH	10.2
Viscosity	1300 mPa.s (Brookfield Spindle 3 @ 20 rpm).
Specific gravity	0.95 (100ml SG Cup)
Suggested coating weight	12 – 15 gsm dry.
Shelf life	Min. 6 months.

## General

### *Hazards:*

Preparations do not carry a hazard classification according to EEC directives 88/379/EEC, 67/548/EEC and 79/831/EEC. May cause soreness if in contact with eyes.

### *Storage:*

Store in tightly closed, original container.

**Protect from frost.**

### *Important Notice:*

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, Tradebond WA889.