



The Glue People

Trade Grade Products Ltd
10 Victory Close
Woolsbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6SX

Tel 01202 820177
Fax 01202 814011

Tradetack

Aerosol Adhesive

General Description

Tradetack is an aerosol adhesive which does not contain CFC's, Methylene chloride or 1.1.1.Trichloroethane. It bonds a wide variety of materials giving a rapid bond formation and is economical in use.

- Halogen and CFC free
- Faster tack
- Foaming formula for low soak-in
- Economical to use
- Variable spray pattern

Tradetack bonds a wide variety of substrates including wood, concrete, stone, tiles, rubber, foams, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork.

It is ideal for fixing polyethylene sheeting for enclosures prior to asbestos removal, for fixing thermal insulation and for packaging applications such as palletising and case sealing.

It may also be used for foam bonding, upholstery, automotive, carpets and trims and is useful for temporary bonding instead of double sided tapes.

Tradetack is not suitable for use with plasticised PVC or expanded polystyrene.

Application

Shake before use. Spray adhesive from 6" to 8" away onto one or both surfaces. Surfaces should be free of dust, dirt, grease and any other contaminants liable to impair adhesion.

For one way applications let the adhesive dry for 30 seconds until tacky, then press into position.

For two way applications, spray both surfaces and allow to dry for 2-5 minutes before bonding.

For temporary bonding, spray one surface and allow to dry for 2-5 minutes before bonding. Excessive adhesive can be removed with a multipurpose cleaner.

Physical Data

Type	Aerosol adhesive
Colour	Straw
Base	Synthetic rubber / resin
Application temperature	+5°C to +40°C
Packaging	500ml cans
Shelf life	12 months in a cool, dry area.

Special comments

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, Tradetack.