



The Glue People

Trade Grade Products Ltd
10 Victory Close
Woolsbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6SX

Tel 01202 820177
Fax 01202 814011

Tradesolve

2

Solvent-borne epoxy cleaner.

General Description

Tradesolve 2 is a highly flammable cleaning solvent designed for cleaning equipment which has been used to apply epoxy resins.

Application

Carefully clean the DeLam TX injection gun using Tradesolve 2 and a small paintbrush. A small amount of solvent can be poured into the barrel of the gun and shaken. Ensure that gloves and eye/face protection is worn at all times. Solvent washings can then be poured into an empty can and allowed to evaporate. Empty solvent cans should be disposed off as hazardous waste.

Physical Data

Base	Aromatic hydrocarbons.
Colour	Colourless (as water).
Odour	Characteristic.
Chemical type	Xylene / I.P.A.
Specific gravity	0.80 @ 20°C.
Flammability	Highly flammable – Flash point below 23°C.
Storage life	1 year. Store in a flame-proof room between 5°C and 25°C.

Special comments

Occasional skin contact with Tradesolve 2 should have no adverse effects. However, prolonged soaking or repeated contact is not recommended.

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.

Before using this product ensure that you have been supplied with and have read carefully the following information.

- The hazard label (complying with latest CDG/CPL regulations) applied to the container.
- Material Safety Data Sheet, Tradesolve 2.